



VELCRO® Brand Hook & Loop Aerospace Matrix

Products	Specifications					Applications
	FAR 25.853, Appendix F, Part 1 (a) (1) (i)	FAR 25.853, Appendix F, Part 1 (a) (1) (ii)	FAR 25.853, Appendix F, Part 1 (a) (1) (iv)	FAR 25.853, Appendix F, Part 1 (a) (1) (v)	FAR 25.856 (a)	
	60 s vertical burn	12 s vertical burn	15 s horizontal burn, 2.5 inches/min max	15 s horizontal burn, 4 inches/min max	Radiant Panel test	
Hook 88 / Loop 1000 - 8289 binder	X	X	X	X	I N D E V E L O P M E N T	Straps and sew-on/textile (seating), customer supplied permanent adhesive applications
Hook 81 / Loop 9000 - 8289 binder		X				Straps and sew-on/textile (seating), customer supplied permanent adhesive applications. Specific to applications requiring moisture, chemical and UV resistance
Hook 88 / Loop 1000 - 8224 adhesive	X	X	X	X		Seating and other trim attachment requiring PS adhesive
Hook 81 / Loop 9000 - 8224 adhesive		X				Seating and other trim attachment requiring PS adhesive. Specific to applications requiring moisture, chemical and UV resistance
ONE-WRAP® 889	X	X				Electrical cable management
HI-AIR®		X				Temperature resistance to 350 deg. F, Aramid fibre
HI-GARDE®	N/A	N/A	N/A	N/A		Temperature resistance to 800 deg. F, 100% stainless steel

Transportation Sales Offices

Americas: 1-248-583-6060

Europe: +34-93-758-3298

Asia Pacific: +852-2570-3698

www.velcro.com